

Lawson Kegs Inc.

BEVERAGE EQUIPMENT

lawsonkegs.com

Let us be your trusted keg service provider.

Canadian owned and operated, we have been specializing in new and used kegs for over 10 years. Lawson Kegs is dedicated to providing customers with quality kegs and exceptional customer service. It's our goal to serve you better than any competitor and provide you with a product that will last. When it comes to your kegs, put your trust in Lawson Kegs Inc.

3 HEAD SEMI AUTOMATIC KEG WASHER

Made in Canada.

Two Station 3 head (2 small kegs can fit in one station), manually loaded and PLC operated keg washer/rinser. Easy to use and fully programmable operator interface for optimum cleaning flexibility and efficiency.

As of March 12/2019, all units come ESA certified. If you are outside Ontario and you do not require or need/want this certification then a discount of \$1600 can be applied.

These washers come with a manual valve that allows for you to clean the spears with a low flow function.



3 HEAD SEMI AUTOMATIC KEG WASHER

EXTENDED INFORMATION

- Add Mixture to tank & put metering pump in sanitizer solution keg provided.
- Plug in Water & Heater
(Heater always on, once plugged in). Do not run dry.
- Plug in the unit to standard A/C plug.
- Connect cold water line-in (45psi) and hot water line-in (45psi).
- Connect water line-out (downward facing barb).
- Connect Air (45psi) & Co2 line (45psi).
- Turn unit on. (Computer is already pre-set, so do not change settings until you are very familiar with the unit).
- Connect the kegs.
(When washing 2 kegs only, shut off one coupler)
- Press the green button to start the cycles.
- Release all/both couplers before un-tapping handles (should be done at the same time).
- Notes: Some models have a blue handled ball valve on the pump which will allow the pump to prime.

FEATURES

- Keg washer designed to purge, drain, Hot caustic wash, hot rinse, sanitation and last co2 charge. PLC system controls each sequence automatically.
- Equipped with 3 couplers.

TECHNICAL SPECS

- Approximate dimensions - 24" D x 48" W x 30"H
- Frame construction, 304 Stainless Steel, polished.
- Washer includes heated 80 Litre /20 Gallon caustic tank, with sight gauge and tank drain valve.
- All control valves 24 VDC stainless steel.
- ½ HP stainless steel housing centrifugal circulation pump.
- Touch screen operator HMI, with automatic and setup controls, housed in stainless steel enclosure.
- Washer equipped with regulators for compressed air and CO2 supply.
- System plumbing 1 ½" Tri-Clamp stainless steel piping.
- Washer equipped with three (3) Sankey keg couplers. Couplers available for other keg styles upon request.
- Electrical requirements: 120 VAC, single phase, 25a
- Plant Water: rinse water, 20 GPM 40-50 PSI
- Plant CO2: 8-15 CFM @ 60 PSI